
GUIDE BUSH, BRONZE WITH SOLID LUBRICANT



2052.70.



Material:

Bronze with solid lubricant, oilless lubricating

Note:

Bushes can be used with radial or axial motion.

Matching guide combinations, see selection matrix at the beginning of chapter D.

 $_{\mbox{\scriptsize cm}}$ Assembly guide lines / Dimensional requirements and tolerances at the end of chapter D.

Attention:

Note that press fitment reduces inside bush diameter.

2052.70. Guide bush, Bronze with solid lubricant


8	10	10	12	13	14	15	16	18	19	20	20	20	24	25	25	25	28	30	30	30	31.5	32	35	35	38	40	40
12	14	15	18	19	20	21	22	24	25	26	28	30	32	32	33	35	38	40	38	42	40	42	44	45	48	50	55
0.5	0.5	0.5	0.5	0.5	0.5	0.75				0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	0.75	1.5	1.5	1.5
2	2	2	2	2	2	2	2	2	2	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
•	•																										
•	•	•	•	•	•	•	•																				
	<u> </u>		<u> </u>		•	<u> </u>	<u> </u>																				
•	•		•	•	•	•	•	•			•	_			_												
				•		•	•	•			•	•				•											
	•		•	•	•	•	•	•			•	•			•	•		•	•					•		•	
			•			•	•	•			•	•			•	•		•	•				•	•		•	•
			•		•	•	•	•			•	•			_	•	•	•	•		•	•	•	•	•	•	•
							•	•			•	•			•	•		•	•				•	•		•	
							_	_	•	_	•	_			_	_	_	_	_		_	_	_	_	_	_	_
							•	•		•	•	•			•	•	•	•	•		•	•	•	•	•	•	
													•	_	•	_		_	_				_	_			
														•		•		•	•	_		_	•	•		•	•
															_			_	_	_		_	_	_		<u> </u>	_
																									_	•	
	12 0.5 2	12 14 0.5 0.5 2 2	12 14 15 0.5 0.5 0.5 2 2 2 2	12 14 15 18 0.5 0.5 0.5 0.5 2 2 2 2 2	12 14 15 18 19 0.5 0.5 0.5 0.5 0.5 2 2 2 2 2 2 2	12 14 15 18 19 20 0.5 0.5 0.5 0.5 0.5 0.5 2 2 2 2 2 2 2 2 0 0 0 0 0 0 0 0 0 0 0 0	12 14 15 18 19 20 21 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.75 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	12 14 15 18 19 20 21 22 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.75 0.75 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	12 14 15 18 19 20 21 22 24 0.5 0.5 0.5 0.5 0.5 0.75 0.75 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	12 14 15 18 19 20 21 22 24 25 0.5 0.5 0.5 0.5 0.5 0.75 0.75 0.75 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	12 14 15 18 19 20 21 22 24 25 26 0.5 0.5 0.5 0.5 0.5 0.5 0.75 0.75 0.75	12 14 15 18 19 20 21 22 24 25 26 28 0.5 0.5 0.5 0.5 0.5 0.5 0.5 0.75 0.75 0	12	12 14 15 18 19 20 21 22 24 25 26 28 30 32 0.5 0.5 0.5 0.5 0.5 0.75 0.75 0.75 0.75	12	12	12 14 15 18 19 20 21 22 24 25 26 28 30 32 32 33 35 0.5 0.5 0.5 0.5 0.5 0.5 0.75 0.75 0.75	12	12	12	12	12	12	12	12	12	12

Ordering Code (example):

Guide bush, Bronze with solid lubricant	=20	52.70.	
Diameter of conduit d ₁	40 mm =	040.	
Outer diameter d ₂	55 mm =	055.	
Installation length I ₁	25 mm =	025	
Order No	=20	52.70. 040. 055.025	

GUIDE BUSH, BRONZE WITH SOLID LUBRICANT

2052.70.





Material:

Bronze with solid lubricant, oilless lubricating

Note:

Bushes can be used with radial or axial motion.

Matching guide combinations, see selection matrix at the beginning

Assembly guide lines / Dimensional requirements and tolerances at the end of chapter D.

Attention:

Note that press fitment reduces inside bush diameter.

2052.70. Guide bush, Bronze with solid lubricant

d.	45	45	45	50	50	50	55	60	60	63	65	70	70	75	75	80	80	85	90	100	110	120	125	130	140	150	160
d_1	56	55	60	60	62	65	70	74	75	75	80	85	90	90	95	96	100	100	110	120	130	140	145	150	160	170	180
α_2											00																
r	1.5	1.5	1.5	1.5	1.5	1.5	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
l ₄	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
Ī ₁																											
30	•	•	•	•	•	•		•	•																		
35	•	•	•	•	•			•	•			•															
40	•	•	•	•	•	•	•	•	•			•				•	•										
50	•	•	•	•	•	•	•	•	•		•	•	•			•	•										
60	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•							
70			•	•	•	•	•	•	•	•	•	•	•	•	•	•	•		•	•							
80			•	•		•		•	•	•	•	•	•	•	•	•	•	•	•	•	•	•					
95				•																							
100						•			•			•		•	•	•	•		•	•	•	•	•	•	•	•	•
120										•						•	•		•	•	•	•	•	•			
130																								•			
140																	•			•		•			•		
150																										•	•

Ordering Code (example):

Guide bush, Bronze with solid lubricant	= 2052.70	0.		
Diameter of conduit d ₁	40 mm =	040.		
Outer diameter d ₂	55 mm =	055.		
Installation length I ₁	25 mm =	025		
Order No	= 2052 70	0 040 055 025		